

STAKING CHART

Initial Staking Chart: Rev. E for Review
Revision: September 2012

SURVEY					FINAL							FOUNDATION TYPE	Leg Extension				Chimney				SECTION LENGTH (M)	FINAL	SPECIAL CROSSING Specification	CONDUCTOR					OPGW					Remarks		
POINT ID	DEVIATION ANGLE				FINAL Ground Elevation	IDENTIFICATION FINAL	Type	Body Ext.	Coordinates		Distance (M)		Final	A	B	C	D	A	B	C				D	DT	ST	DS	SS	DAMPER	ATTACHMENT Quantity					VIBRATION DAMPER	SPLICE BOX
									Easting	Northing																				T with Box	T without Box	SS	End			
AP5						37	T	3	274023,820	9885169,430		T																1			1				1	
											344,972																									
						38	S	0	273925,890	9885500,210		S	-	-	-	-	500	500	500	800																
											214,113																									
						39	S	6	273865,430	9885705,610		S	-	+1	-	-	1000	500	1000	500																
						40	S	3	273761,960	9886056,560		S	-	-	-	-	500	500	800	1100																
											248,336																									
						41	S	3	273691,681	9886294,744		S	-	-	-	-	700	1000	500	500																
						42	S	0	273612,450	9886563,530		S	-	-	-	-	500	1000	1000	500																
											333,051																									
	48	17	35	R		43	H	0	273518,280	9886882,990		T	-	-	-	+1	800	500	1000	500																
											179,852																									
						44	S	6	273613,352	9887035,660		S	+1	+1	-	-	500	800	1000	500																
											355,012																									
						45	S	3	273800,789	9887337,158		S	-	-	+1	+1	500	500	500	500																
											250,007																									
						46	S	0	273932,786	9887549,479		S	-	-	-	-	500	600	700	600																
											273,613																									
						47	S	0	274077,246	9887781,848		S	-	-	-	-	600	600	500	500																
											173,477																									
	10	34	24	L		48	L	3	274168,747	9887929,231		L	-	-	-	-	500	1000	1000	500																
											365,175																									
						49	S	6	274300,810	9888269,690		S	-	-	-	+1	1000	500	1000	800																
											250,165																									
						50	S	0	274391,980	9888502,650		S	-	-	-	-	500	500	500	500																
											256,238																									
	11	58	47	R		51	L	0	274485,250	9888741,310		L	-	-	-	-	500	500	500	500																
											305,664																									
						52	S	6	274653,790	9888996,310		S	+1	+1	-	-	500	500	500	500																
											364,323																									
						53	S	0	274852,840	9889301,450		S	-	-	-	-	500	600	500	500																
											177,151																									
						54	S	3	274950,030	9889449,560		S	-	-	-	-	1000	1000	500	500																
											381,389																									
						55	S	3	275159,280	9889768,420		S	-	-	-	-	1000	500	500	1000																
											253,529																									

[illegible]

[illegible]

[illegible]

[illegible]

